

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

WHAT IS CLAIMED IS:

1. A phase comparator comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

2. A low pass filter comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

3. A voltage controlled oscillator comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel

formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

4. A frequency divider comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

5. An oscillator for a source line driver comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

6. An oscillator for a gate line driver comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

7. A digital-to-analog converter comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

8. A pixel matrix circuit comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

9. A source line driver circuit comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

10. A gate line driver circuit comprising:

a semiconductor film provided over a silicon wafer and comprising a source region, a drain region and a channel

formation region provided between said source region and said drain region; and

a gate electrode provided adjacent to said channel formation region with a gate insulating film therebetween,

wherein lattices are continuously connected to each other at grain boundary of said semiconductor film according to high resolution TEM.

11. A phase comparator according to claim 1 wherein said phase comparator is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

12. A low pass filter according to claim 2 wherein said low pass filter is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

13. A voltage controlled oscillator according to claim 3 wherein said voltage controlled oscillator is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer,

a portable information terminal, a system display, a mobile computer and a portable telephone.

14. A frequency divider according to claim 4 wherein said frequency divider is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

15. An oscillator for a source line driver according to claim 5 wherein said oscillator is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

16. An oscillator for a gate line driver according to claim 6 wherein said oscillator is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

17. A digital-to-analog converter according to claim 7 wherein said digital-to-analog converter is incorporated

into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

18. A pixel matrix circuit according to claim 8 wherein said pixel matrix circuit is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

19. A source line driver circuit according to claim 9 wherein said source line driver circuit is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.

20. A gate line driver circuit according to claim 10 wherein said gate line driver circuit is incorporated into at least one of a video camera, a still camera, a head mount display, a car navigation system, a personal computer, a portable information terminal, a system display, a mobile computer and a portable telephone.